

APPLICANT(S): SALI et al.  
SERIAL NO.: 10/627,980  
FILED: July 28, 2003  
Page 2

### AMENDMENTS TO THE CLAIMS

Kindly amend the claims as follows:

1-4. (Withdrawn)

5. (Currently Amended): A calibration unit for a color bar code system, the calibration unit comprising:

a color chart generator to generate at least one color chart of color patches of the N bar code colors utilized by said color bar code system; and

a color calibrator to receive ~~the~~a design of said color chart from said generator and ~~the~~an output of a camera reader upon reading said color chart under varying conditions and to associate said output corresponding to each said color patch, per condition, with one of said N bar code colors.

6. (Original): A unit according to claim 5 and also comprising a color classifier to associate each data point in a color space with one of said N bar code colors using the output of said color calibrator.

7. (Original): A unit according to claim 6 and wherein said color classifier comprises a k-nearest neighbor classifier.

8. (Original): A unit according to claim 7 wherein said k-nearest neighbor classifier comprises:

neighbor extracting means for finding at least k neighboring training vectors of a test point and for extracting the bar code color associated with each said neighbor;

majority defining means for weighting said bar code colors of said neighboring training vectors by the ratio of said bar code colors within the entirety of said training vectors and for selecting a majority bar code color;



APPLICANT(S): SALI et al.  
SERIAL NO.: 10/627,980  
FILED: July 28, 2003  
Page 3

means for activating said neighbor extracting means and said majority defining means on  $k/2$  and  $2k$  vectors, if no majority was found; and  
means for selecting a majority bar code color from the output of said majority defining means upon each of said  $k$ ,  $k/2$  and  $2k$  operations.

9. (Original): A unit according to claim 8 wherein said neighbor extracting means comprises:

means for extracting all training vectors within a minimum radius;  
means for extracting a minimum of  $k$  nearest neighbors within a maximum radius;  
means for extracting  $k/2$  neighbors from the entire color space; and  
means for activating each of said means for extracting until at least  $k$  neighbors have been extracted.

10-13. (Withdrawn)

14. (Currently Amended): A method comprising:

generating at least one color chart of color patches of the  $N$  bar code colors utilized by a color bar code system; and  
associating ~~the~~an output of a camera reader upon reading said color chart under varying conditions with said  $N$  bar code colors, wherein said output includes a data point per color patch and per condition.

15. (Original): A method according to claim 14 and also comprising associating each data point in a color space with one of said  $N$  bar code colors using the output of said first step of associating.

16. (Original): A method according to claim 15 and wherein said second associating comprises  $k$ -nearest neighbor classifying.



APPLICANT(S): SALI et al.  
SERIAL NO.: 10/627,980  
FILED: July 28, 2003  
Page 4

17. (Original): A method according to claim 16 wherein said k-nearest neighbor classifying comprises:

- finding at least k neighboring training vectors of a test point;
- extracting the bar code color associated with each said neighbor;
- weighting said bar code colors of said neighboring training vectors by the ratio of said bar code colors within the entirety of said training vectors;
- selecting a majority bar code color;
- repeating said finding, extracting, weighting and selecting on  $k/2$  and  $2k$  vectors, if no majority was found; and
- selecting a majority bar code color from the output of said repeating upon each of said  $k$ ,  $k/2$  and  $2k$  operations.

18. (Original): A method according to claim 17 wherein said finding comprises:

- extracting all training vectors within a minimum radius;
- extracting a minimum of k nearest neighbors within a maximum radius;
- extracting  $k/2$  neighbors from the entire color space; and
- repeating said first, second and third steps of extracting until at least k neighbors have been extracted.